



PROWALL 2000 SEMI-GLOSS INTERIOR LATEX ENAMEL 2590, 2592

Resin Type	Sheen	Quality Level	Spread Rate	Clean Up	Thinner	Dry at 77°F.	V.O.C. Level
vinyl acrylic latex	semi-gloss	professional best	400-450 sq. ft./gal. (on smooth surfaces)	water	water	1 hour tack free 4 hours recoat	< 380 g/L

Description

ProWall 2000 is a low-odor semi-gloss wall interior latex enamel which gives you all the advantages of conventional enamels, plus the fast dry and easy clean up of latex. Formulated to provide toughness and scrubability with easy application. Provides excellent hide and leveling qualities.

Where To Use

This product is designed for interior use on properly primed wood, plaster, wallboard, concrete and metal surfaces. Ideal for kitchen, bath and all walls and surfaces subjected to heavy wear and frequent washing. Especially durable for commercial office applications.

Surface Preparation

New Work - Allow new plaster or taped wallboard to dry thoroughly before priming with interior latex primer. Sand and prime new woodwork. Seal any knots or resinous areas thoroughly. Two coats of #2590 are normally recommended on new wood.

Old Work - Remove all loose, old paint, oil, dirt, wax and grease from the surface. Lightly sand glossy areas. Fill all holes with spackling compound. After drying, sand smooth and spot prime with Latex Primer #1250.

Concrete - Allow concrete to cure thoroughly before application. Remove any efflorescence. At least two coats are recommended.

Primer

Sheetrock - Use #1250 Latex Primer or #1255 PVA Primer.

Plaster - Use #1250 Latex Primer or #1255 PVA Primer.

New Wood - Use #9004 Alkyd Undercoater.

Metal - Use #9250 Metal Primer.

Old Painted Surfaces - Spot prime porous areas with #1250 Latex Primer or #1255 PVA Primer.

New Masonry - Use #1450 Latex Block Filler.

Application

Stir contents thoroughly before and during application. Apply generously. This product may be brushed, rolled or sprayed. Do not apply below 50°F or above 90°F. Keep a wet edge to avoid lap marks.

Recommended Wet Film Per Coat: 3.5 mils.

Recommended Dry Film Per Coat: 1 mils.

Available Colors

White, pastel and mid-tone colors.

Caution

Keep from freezing.
See other cautions on back.

Environmentally Friendly Tips

- Only purchase the quantity you need.
- Do not mix paints for storage or disposal. Leave paint in the original container.
- Do not throw liquid paint in the trash or pour it down the drain.
- Small amounts of latex paint can be air-dried and disposed through your trash collection system.
- Recycle leftover or unused paint. Call your local government for recycling advice.

Packaging Options

- Five gallon pails
- Gallons

Physical Data

(figures shown are approximate)

Solids by Weight	45%
Solids by Volume	32%
Weight per Gallon	10.33
Viscosity	95 KU
Gloss @ 60°	20-25
Flashpoint	Over 200°F
Flow and Leveling (ASTM D4062)	9
Spattering Rating (ASTM D4707)	9
Sag Rating (ASTM D4400)	> 12 mils
Hegman Grind (ASTM D1210)	6

Limitations

Not recommended for use on the following:

- floors or other horizontal surfaces
- areas of corrosive chemical environments
- rusted substrates without adequate surface preparation and must be primed to minimize rust staining through the topcoat.

Excessive color tinting may cause unsatisfactory drying. Since these are water base coatings, dry time will be affected by temperature and humidity.

Not recommended for immersion service or use on damp or wet surfaces, high heat, or humid conditions.

Health And Environment

This material contains no lead, mercury or crystalline silica. Material Safety Data Sheets are available upon request. When

Precautionary Information

In all cases, please read respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, and how it should be properly fitted.

Some of the components of various coatings may be irritating to the skin and/or eyes, so contact should be prevented. In case of contact, flush skin thoroughly with soap and water. For eyes, flush with plenty of water for at least 15 minutes and get medical attention immediately.

During the application of all coating materials, all flames, welding and smoking must be prohibited.

Before using the products listed herein, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels.

CAUTION! DO NOT TAKE INTERNALLY! CLOSE CONTAINER AFTER EACH USE! KEEP OUT OF THE REACH OF CHILDREN!

Avoid prolonged breathing of vapor and spray mist. Coatings should only be applied when ventilation is adequate. When available ventilation may not be adequate, applicators should wear respiratory protection, choosing the proper respirator with aid of the following:

Outdoor or open areas: Use filter type respirators (approved with NIOSH/MSHA) to remove solid airborne particulates from overspray.

Restricted ventilation areas: Use combination organic vapor-filter type respirators (approved with NIOSH/MSHA) which are designed to purify the air by removing solid airborne particulates and organic vapors.

Confined areas: Use supplied air respirators or hoods (approved with NIOSH/MSHA)

IMPORTANT! When applying coatings by spray equipment, observe all precautionary safety measures. Spray equipment must be handled with due care and in strict accordance with manufacturer's recommendations for personal safety, and to prevent fire. If precautions are not taken, spraying of any material can be hazardous, particularly when using high pressure airless equipment. High pressure may inject coating into the skin causing serious injury, requiring immediate poison center contact and/or hospital treatment. When using or handling spray equipment hoses and the like, observe all required safety practices. In addition, when spraying paint or coatings, wear a respirator recommended for the product being handled. In all cases, wear protective eye equipment.

First Aid Statement

If swallowed, do induce vomiting. In case of skin contact, wash affected area with mild soap and water. In case of eye contact, flush eyes immediately with plenty of water for 15 minutes. If affected by inhalation of vapor or spray mist, remove to fresh air. Apply artificial respiration and other supportive measures as required. If any of the following occur during or following use of this product, contact a **POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY** (have label information available):

- Ingestion
- Excessive exposure to a corrosive material
- Persistent skin/eye irritation or breathing difficulties
- Other symptoms

10/27/04

spraying, use suitable respiratory protection and provide adequate ventilation. Disposal of most latex paints is allowable in landfills if material is in solid form. Always check with local regulations. Leftover Latex paint is recycable. Contact your local government recycling program for more information.

WARNING: This product complies with Federal law restricting the presence of lead in consumer coatings. Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. EXPOSURE TO LEAD DUST OR FUMES MAY CAUSE ADVERSE HEALTH EFFECTS, ESPECIALLY IN CHILDREN OR PREGNANT WOMEN. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. for additional information, contact the USEPA/Lead Information Hotline at 1-800-424-LEAD.

Medical Response

Emergency Medical Information 1-800-535-5053

The facts and figures represented in the specification manual are accurate to the best of our knowledge, and are the results of testing in our laboratory. We do not express, warrant or guarantee the accuracy, completeness, or reliability of same. Since Hirshfield's paint Mfg. is constantly improving its products, future technical data may vary somewhat from what was available when this bulletin was printed.

Corporate Office/Retail/Support Center
725 Second Ave. N., Mpls., MN 55405

612-377-3910 • www.hirshfields.com • e-mail: info@hirshfields.com



Hirshfield's Paint Mfg., Inc.

4450 Lyndale Ave. No. Mpls., MN 55412 / (612) 522 6621